

## MAZDA

※実車上で交換可能なクーラント量は全容量の80%程度となります。

| 車両         | 排気量  | 車両型式        | エンジン                        | 年式          | 冷却水全量A | Aの80%量 | 31%(-15度)<br>になる抜量 | 全交換40%<br>クーラント量 | 全交換40%の水量 | 備考       |
|------------|------|-------------|-----------------------------|-------------|--------|--------|--------------------|------------------|-----------|----------|
| AZオフロード    | 660  | JM23W       | K6A(DOHC)                   | 98/10～12/3  | 4      | 3.2    | 0.90               | 1.28             | 1.92      |          |
| AZ OFFROAD | 660  | JM23W       | K6A(DOHC,TURBO)             | 98/10～12/3  | 4      | 3.2    | 0.90               | 1.28             | 1.92      |          |
| AZワゴン      | 660  | MJ23S       | K6A(TURBO)                  | 08/9～12/9   | 3.4    | 2.72   | 0.77               | 1.09             | 1.63      |          |
| AZ WAGON   | 660  | MJ23S       | K6A(DOHC)                   | 08/9～12/9   | 3      | 2.4    | 0.68               | 0.96             | 1.44      | MT       |
|            |      |             |                             |             | 3.3    | 2.64   | 0.74               | 1.06             | 1.58      | AT       |
|            |      |             |                             |             | 3.2    | 2.56   | 0.72               | 1.02             | 1.54      | CVT      |
|            | 660  | MJ22S       | K6A(DOHC,TURBO)             | 07/2～08/8   | 3.5    | 2.8    | 0.79               | 1.12             | 1.68      |          |
|            | 660  | MJ22S       | K6A(DOHC)                   | 07/2～08/8   | 3      | 2.4    | 0.68               | 0.96             | 1.44      | MT       |
|            |      |             |                             |             | 3.3    | 2.64   | 0.74               | 1.06             | 1.58      | AT       |
|            |      |             |                             |             | 3.2    | 2.56   | 0.72               | 1.02             | 1.54      | CVT      |
|            | 660  | MJ21S       | K6A(DOHC,TURBO)             | 03/9～07/2   | 3.5    | 2.8    | 0.79               | 1.12             | 1.68      |          |
|            | 660  | MJ21S       | K6A(DOHC)                   | 03/9～07/2   | 3      | 2.4    | 0.68               | 0.96             | 1.44      | MT       |
|            |      |             |                             |             | 3.3    | 2.64   | 0.74               | 1.06             | 1.58      | AT       |
| CX-3       | 1500 | DKLFY.DKLAY | P5-VPS                      | 22/2～       | 5.3    | 4.24   | 1.19               | 1.70             | 2.54      |          |
|            | 1500 | DKLFW.DKLAW | P5-VPS                      | 20/2～22/1   | 5.3    | 4.24   | 1.19               | 1.70             | 2.54      |          |
|            | 1500 | DK5FW.DK5AW | S5-DPTS,S5-DPTR             | 15/5～18/4   | 6.6    | 5.28   | 1.49               | 2.11             | 3.17      | MT       |
|            |      |             |                             |             | 6.8    | 5.44   | 1.53               | 2.18             | 3.26      | AT       |
|            |      |             |                             |             | 2.1    | 1.68   | 0.47               | 0.67             | 1.01      | インタークーラー |
|            | 1800 | DK8FY.DK8AY | S8-DPTS                     | 22/2～       | 6.6    | 5.28   | 1.49               | 2.11             | 3.17      | MT       |
|            |      |             |                             |             | 6.7    | 5.36   | 1.51               | 2.14             | 3.22      | AT       |
|            |      |             |                             |             | 2      | 1.6    | 0.45               | 0.64             | 0.96      | インタークーラー |
|            | 1800 | DK8FW.DK8AW | S8-DPTS,S8-DPTR             | 18/5～22/1   | 6.6    | 5.28   | 1.49               | 2.11             | 3.17      | MT       |
|            |      |             |                             |             | 6.7    | 5.36   | 1.51               | 2.14             | 3.22      | AT       |
|            |      |             |                             |             | 2      | 1.6    | 0.45               | 0.64             | 0.96      | インタークーラー |
|            | 2000 | DKEFW.DKEAW | PE-VPS                      | 17/6～22/1   | 5.9    | 4.72   | 1.33               | 1.89             | 2.83      |          |
| CX-5       | 2500 | KF5P        | PY-VPTS (TURBO)             | 18/11～      | 8.7    | 6.96   | 1.96               | 2.78             | 4.18      |          |
|            | 2000 | KFEP        | PE-VPS                      | 18/2～       | 7.2    | 5.76   | 1.62               | 2.30             | 3.46      |          |
|            | 2200 | KF2P        | SH-VPTS(SKYACTIV-D)         | 18/2～       | 8.7    | 6.96   | 1.96               | 2.78             | 4.18      |          |
|            | 2000 | KFEP        | PE-VPS                      | 17/1～18/1   | 7.1    | 5.68   | 1.60               | 2.27             | 3.41      |          |
|            | 2200 | KF2P        | SH-VPTS(SKYACTIV-D)         | 17/1～18/1   | 8.9    | 7.12   | 2.00               | 2.85             | 4.27      |          |
|            | 2500 | KF5P        | PY-VPS                      | 17/1～       | 7.2    | 5.76   | 1.62               | 2.30             | 3.46      |          |
|            | 2500 | KE5FW.KE5AW | PY-VPS                      | 13/10～16/12 | 7.3    | 5.84   | 1.64               | 2.34             | 3.50      |          |
|            | 2000 | KEEFW.KEEAW | PE-VPS                      | 12/2～16/12  | 7.2    | 5.76   | 1.62               | 2.30             | 3.46      |          |
| CX-7       | 2200 | KE2FW.KE2AW | SH-VPTS(SKYACTIV-D)         | 12/2～16/12  | 9.2    | 7.36   | 2.07               | 2.94             | 4.42      |          |
|            | 2300 | ER3P        | L3-VDT(TURBO)               | 06/12～11/12 | 9      | 7.2    | 2.03               | 2.88             | 4.32      |          |
| CX-8       | 2500 | KG5P        | PY-VPS(SKYACTIV)            | 18/11～      | 8.4    | 6.72   | 1.89               | 2.69             | 4.03      |          |
|            | 2500 | KG5P        | PY-VPTS (TURBO)             | 18/11～      | 9.7    | 7.76   | 2.18               | 3.10             | 4.66      |          |
|            | 2200 | KG2P        | SH-VPTS                     | 17/9～       | 9.8    | 7.84   | 2.21               | 3.14             | 4.70      |          |
| CX-30      | 1800 | DM8R        | S8-DPTS                     | 23/10-      | 7      | 5.6    | 1.58               | 2.24             | 3.36      |          |
|            |      |             |                             |             | 1.6    | 1.28   | 0.36               | 0.51             | 0.77      | インタークーラー |
|            | 1800 | DM8P        | S8-DPTS                     | 19/09-23/09 | 7      | 5.6    | 1.58               | 2.24             | 3.36      |          |
|            |      |             |                             |             | 1.6    | 1.28   | 0.36               | 0.51             | 0.77      | インタークーラー |
|            | 2000 | DMEJ3R      | PE-VPS                      | 23/10-      | 5.9    | 4.72   | 1.33               | 1.89             | 2.83      |          |
|            | 2000 | DMFP        | HF-VPH                      | 20/01-23/09 | 6.9    | 5.52   | 1.55               | 2.21             | 3.31      | MT       |
|            |      |             |                             |             | 7      | 5.6    | 1.58               | 2.24             | 3.36      | AT       |
|            |      |             |                             |             | 1.6    | 1.28   | 0.36               | 0.51             | 0.77      | インタークーラー |
| CX-60      | 2000 | DMEP        | PE-VPS                      | 19/09-23/09 | 6.2    | 4.96   | 1.40               | 1.98             | 2.98      | MT       |
|            |      |             |                             |             | 6.4    | 5.12   | 1.44               | 2.05             | 3.07      | AT       |
|            | 2500 | KH5P        | PY-VPS                      | 22/09-      | 6.5    | 5.2    | 1.46               | 2.08             | 3.12      |          |
|            |      |             |                             |             | 3.6    | 2.88   | 0.81               | 1.15             | 1.73      | AT冷却液    |
|            |      |             |                             |             | 8.6    | 6.88   | 1.94               | 2.75             | 4.13      |          |
|            | 2500 | KH5S3P      | PY-VPH                      | 22/09-      | 6.4    | 5.12   | 1.44               | 2.05             | 3.07      | EVシステム   |
|            | 3300 | KH3P        | T3-VPTS                     | 22/09-      | 8.4    | 6.72   | 1.89               | 2.69             | 4.03      |          |
|            |      |             |                             |             | 4.9    | 3.92   | 1.10               | 1.57             | 2.35      | インタークーラー |
| MAZDA 2    | 3300 | KH3R3P      | T3-VPTH                     | 22/09-      | 8.4    | 6.72   | 1.89               | 2.69             | 4.03      |          |
|            |      |             |                             |             | 5.8    | 4.64   | 1.31               | 1.86             | 2.78      | インタークーラー |
|            |      |             |                             |             | 4.8    | 3.84   | 1.08               | 1.54             | 2.30      | MT       |
|            | 1500 | DJLFS,DJLAS | P5-VPS                      | 19/09-      | 5.1    | 4.08   | 1.15               | 1.63             | 2.45      | AT       |
|            | 1500 | DJ5FS.DJ5AS | S5-DPTS,S5-DPTR(SKYACTIV-D) | 19/09-      | 6.6    | 5.28   | 1.49               | 2.11             | 3.17      | MT       |
|            |      |             |                             |             | 6.8    | 5.44   | 1.53               | 2.18             | 3.26      | AT       |
|            |      |             |                             |             | 2      | 1.6    | 0.45               | 0.64             | 0.96      | インタークーラー |
|            | 2000 | BPFJ3R      | PE-VPH                      | 23/06-      | 5.9    | 4.72   | 1.33               | 1.89             | 2.83      | AT       |
| MAZDA 3    | 1500 | BP5R        | P5-VPS                      | 23/06-      | 5.4    | 4.32   | 1.22               | 1.73             | 2.59      |          |
|            | 1500 | BP5P        | P5-VPS                      | 19/05-23/05 | 5.6    | 4.48   | 1.26               | 1.79             | 2.69      | MT       |
|            |      |             |                             |             | 5.9    | 4.72   | 1.33               | 1.89             | 2.83      | AT       |
|            | 1800 | BP8R        | S8-DPTS                     | 23/06-      | 7      | 5.6    | 1.58               | 2.24             | 3.36      |          |
|            |      |             |                             |             | 1.6    | 1.28   | 0.36               | 0.51             | 0.77      | インタークーラー |
|            | 1800 | BP8P        | S8-DPTS                     | 19/05-23/05 | 7      | 5.6    | 1.58               | 2.24             | 3.36      |          |
|            |      |             |                             |             | 1.6    | 1.28   | 0.36               | 0.51             | 0.77      | インタークーラー |
|            | 2000 | BPFJ3R      | PE-VPH                      | 23/06-      | 5.7    | 4.56   | 1.28               | 1.82             | 2.74      | MT       |
|            |      |             |                             |             | 5.9    | 4.72   | 1.33               | 1.89             | 2.83      | AT       |

|                          |        |             |                     |             |      |      |      |      |      |          |
|--------------------------|--------|-------------|---------------------|-------------|------|------|------|------|------|----------|
|                          | 2000   | BPEK3R      | HF-VPH              | 23/06-      | 6.9  | 5.52 | 1.55 | 2.21 | 3.31 | MT       |
|                          |        |             |                     |             | 7    | 5.6  | 1.58 | 2.24 | 3.36 | AT       |
|                          |        |             |                     |             | 1.6  | 1.28 | 0.36 | 0.51 | 0.77 | インタークーラー |
|                          | 2000   | BPFJ3P      | PE-VPS              | 22/09-23/05 | 5.7  | 4.56 | 1.28 | 1.82 | 2.74 | MT       |
|                          |        |             |                     |             | 5.9  | 4.72 | 1.33 | 1.89 | 2.83 | AT       |
|                          | 2000   | BFPF        | PE-VPS              | 19/05-22/08 | 6.4  | 5.12 | 1.44 | 2.05 | 3.07 |          |
|                          | 2000   | BPEP        | HF-VPH              | 19/12-23/05 | 6.9  | 5.52 | 1.55 | 2.21 | 3.31 | MT       |
|                          |        |             |                     |             | 7    | 5.6  | 1.58 | 2.24 | 3.36 | AT       |
|                          |        |             |                     |             | 1.6  | 1.28 | 0.36 | 0.51 | 0.77 | インタークーラー |
| MAZDA 6 セダン              | 2200   | GJ2FP.GJ2AP | SH-VPTR(SKYACTIV-D) | 19/08-      | 8.6  | 6.88 | 1.94 | 2.75 | 4.13 |          |
| MAZDA 6 SEDAN            | 2500   | GJ5FP       | PY-VPTS (TURBO)     | 19/08-      | 8.6  | 6.88 | 1.94 | 2.75 | 4.13 |          |
|                          | 2500   | GJ5FP       | PY-RPR              | 19/08-      | 6.9  | 5.52 | 1.55 | 2.21 | 3.31 |          |
|                          | 2000   | GJEFP       | PE-VPR              | 19/08-      | 6.8  | 5.44 | 1.53 | 2.18 | 3.26 |          |
| MAZDA 6 ワゴン              | 2200   | GJ2FW.GJ2AW | SH-VPTR(SKYACTIV-D) | 19/08-      | 8.6  | 6.88 | 1.94 | 2.75 | 4.13 |          |
| MAZDA 6 WAGON            | 2500   | GJ5FW       | PY-VPTS (TURBO)     | 19/08-      | 8.6  | 6.88 | 1.94 | 2.75 | 4.13 |          |
|                          | 2500   | GJ5FW       | PY-RPR              | 19/08-      | 6.9  | 5.52 | 1.55 | 2.21 | 3.31 |          |
|                          | 2000   | GJEFW       | PE-VPR              | 19/08-      | 6.8  | 5.44 | 1.53 | 2.18 | 3.26 |          |
| MPV                      | 2300   | LY3P        | L3-VE               | 06/2～       | 10.5 | 8.4  | 2.36 | 3.36 | 5.04 |          |
|                          | 2300   | LY3P        | L3-VDT(TURBO)       | 06/2～       | 10.7 | 8.56 | 2.41 | 3.42 | 5.14 |          |
| MX-30                    | 2000   | DREJ3P      | PE-VPH              | 20/10～      | 6.5  | 5.2  | 1.46 | 2.08 | 3.12 |          |
| RX-7                     | ROTARY | FD3S        | 13B-REW(TURBO)      | 91/12～02/8  | 8.8  | 7.04 | 1.98 | 2.82 | 4.22 |          |
|                          | ROTARY | FC3S.FC3C   | 13B(TURBO)          | 85/10～91/12 | 8.7  | 6.96 | 1.96 | 2.78 | 4.18 |          |
| RX-8                     | ROTARY | SE3P        | 13B-MSP             | 03/4～12/6   | 9.8  | 7.84 | 2.21 | 3.14 | 4.70 |          |
| アクセラ<br>AXELA            | 1500   | BMLFP       | S5-DPTS(SKYACTIV-D) | 17/9～19/4   | 7    | 5.6  | 1.58 | 2.24 | 3.36 |          |
|                          |        |             |                     |             | 1.8  | 1.44 | 0.41 | 0.58 | 0.86 | インタークーラー |
|                          | 2200   | BM2FP.BM2AP | SH-VPTR(SKYACTIV-D) | 16/7～19/4   | 8.9  | 7.12 | 2.00 | 2.85 | 4.27 |          |
|                          | 1500   | BM5FP       | P5-VPS              | 13/11～19/4  | 5.6  | 4.48 | 1.26 | 1.79 | 2.69 | MT       |
|                          |        |             |                     |             | 5.8  | 4.64 | 1.31 | 1.86 | 2.78 | AT       |
|                          | 1500   | BM5AP       | P5-VPS              | 13/11～19/4  | 5.9  | 4.72 | 1.33 | 1.89 | 2.83 |          |
|                          | 2000   | BYEFP       | PE-VPH(HYBRID)      | 13/11～19/4  | 6.4  | 5.12 | 1.44 | 2.05 | 3.07 |          |
|                          | 2000   | BLFFP       | PE-VPS(SKYACTIV)    | 11/9～13/10  | 8.1  | 6.48 | 1.82 | 2.59 | 3.89 |          |
|                          | 1500   | BL5FP       | ZY-VE               | 09/6～13/11  | 6    | 4.8  | 1.35 | 1.92 | 2.88 |          |
|                          | 2000   | BLEFP       | LF-VDS              | 09/6～13/10  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2000   | BLEAP       | LF-VE               | 09/6～13/10  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2000   | BKEP        | LF-DE,LF-VE         | 06/6～13/10  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 1500   | BK5P        | ZY-VE               | 03/10～09/6  | 6    | 4.8  | 1.35 | 1.92 | 2.88 |          |
|                          | 2300   | BK3P        | L3-VE               | 03/10～09/6  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
| アクセラスポーツ<br>AXELA SPORT  | 1500   | BMLFS       | S5-DPTS(SKYACTIV-D) | 16/7～19/4   | 7    | 5.6  | 1.58 | 2.24 | 3.36 |          |
|                          |        |             |                     |             | 1.8  | 1.44 | 0.41 | 0.58 | 0.86 | インタークーラー |
|                          | 2200   | BM2FS       | SH-VPTR(SKYACTIV-D) | 14/1～19/4   | 8.7  | 6.96 | 1.96 | 2.78 | 4.18 | MT       |
|                          |        |             |                     |             | 8.9  | 7.12 | 2.00 | 2.85 | 4.27 | AT       |
|                          | 1500   | BM5FS       | P5-VPS              | 13/11～19/4  | 5.6  | 4.48 | 1.26 | 1.79 | 2.69 | MT       |
|                          |        |             |                     |             | 5.8  | 4.64 | 1.31 | 1.86 | 2.78 | AT       |
|                          | 1500   | BM5AS       | P5-VPS              | 13/11～19/4  | 5.9  | 4.72 | 1.33 | 1.89 | 2.83 |          |
|                          | 2000   | BMEFS       | PE-VPR              | 13/11～16/6  | 6.1  | 4.88 | 1.37 | 1.95 | 2.93 | MT       |
|                          |        |             |                     |             | 6.4  | 5.12 | 1.44 | 2.05 | 3.07 | AT       |
|                          | 2000   | BLFFW       | PE-VPS(SKYACTIV)    | 11/9～13/11  | 8.1  | 6.48 | 1.82 | 2.59 | 3.89 |          |
|                          | 1500   | BL5FW       | ZY-VE               | 09/6～13/11  | 6    | 4.8  | 1.35 | 1.92 | 2.88 |          |
|                          | 2000   | BLEAW       | LF-VE               | 09/6～13/11  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2000   | BLEFW       | LF-VDS              | 09/6～11/8   | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 1500   | BK5P        | ZY-VE               | 03/10～09/6  | 6    | 4.8  | 1.35 | 1.92 | 2.88 |          |
|                          | 2000   | BKEP        | LF-DE               | 03/10～09/6  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2300   | BK3P        | L3-VE               | 03/10～09/6  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
| アテンザ                     | 2200   | GJ2FP.GJ2AP | SH-VPTR(SKYACTIV-D) | 18/5～19/7   | 8.6  | 6.88 | 1.94 | 2.75 | 4.13 |          |
| ATENZA                   | 2500   | GJ5FP       | PY-RPR              | 18/5～19/7   | 6.9  | 5.52 | 1.55 | 2.21 | 3.31 |          |
|                          | 2000   | GJEFP       | PE-VPR              | 12/11～19/7  | 6.8  | 5.44 | 1.53 | 2.18 | 3.26 |          |
|                          | 2200   | GJ2FP.GJ2AP | SH-VPTR(SKYACTIV-D) | 12/11～18/4  | 8.8  | 7.04 | 1.98 | 2.82 | 4.22 | MT       |
|                          |        |             |                     |             | 9.1  | 7.28 | 2.05 | 2.91 | 4.37 | AT       |
|                          | 2500   | GJ5FP       | PY-VPR              | 12/11～18/4  | 6.9  | 5.52 | 1.55 | 2.21 | 3.31 |          |
|                          | 2000   | GHEFP       | LF-VD               | 10/1～12/11  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2500   | GH5FP.GH5AP | L5-VE               | 08/1～12/11  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2000   | GHEFP       | LF-VE               | 08/1～10/1   | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2000   | GGEP        | LF-DE               | 02/5～07/12  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
| アテンザスポーツ<br>ATENZA SPORT | 2300   | GG3P        | L3-VE               | 02/5～07/12  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2500   | GH5FS.GH5AS | L5-VE               | 08/1～12/11  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2000   | GHEFS       | LF-VE               | 08/1～10/1   | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2000   | GGES        | LF-DE               | 02/5～07/12  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |
|                          | 2300   | GG3S        | L3-VE               | 02/5～07/12  | 7.5  | 6    | 1.69 | 2.40 | 3.60 |          |

|                                |                                |                 |                             |             |           |       |           |             |      |      |             |      |
|--------------------------------|--------------------------------|-----------------|-----------------------------|-------------|-----------|-------|-----------|-------------|------|------|-------------|------|
| アテンザ<br>WAGON                  | 2200                           | GJ2FW.GJ2AW     | SH-VPTR(SKYACTIV-D)         | 18/5～19/7   |           | 8.6   | 6.88      | 1.94        | 2.75 | 4.13 |             |      |
|                                | 2500                           | GJ5FW           | PY-RPR                      | 18/5～19/7   |           | 6.9   | 5.52      | 1.55        | 2.21 | 3.31 |             |      |
|                                | 2000                           | GJEFW           | PE-VPR                      | 12/11～19/7  |           | 6.8   | 5.44      | 1.53        | 2.18 | 3.26 |             |      |
|                                | 2200                           | GJ2FW.GJ2AW     | SH-VPTR(SKYACTIV-D)         | 12/11～18/4  |           | 8.8   | 7.04      | 1.98        | 2.82 | 4.22 | MT          |      |
|                                |                                |                 |                             |             |           | 9.1   | 7.28      | 2.05        | 2.91 | 4.37 | AT          |      |
|                                | 2500                           | GJ5FW           | PY-VPR                      | 12/11～18/4  |           | 6.9   | 5.52      | 1.55        | 2.21 | 3.31 |             |      |
|                                | 2000                           | GHEFW           | LF-VD                       | 10/1～12/11  |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 |             |      |
|                                | 2500                           | GH5FW.GH5AW     | L5-VE                       | 08/1～12/11  |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 |             |      |
|                                | 2000                           | GHEFW           | LF-VE                       | 08/1～10/1   |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 |             |      |
|                                | 2000                           | GYEW            | LF-DE                       | 02/5～07/12  |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 |             |      |
| キャロル<br>CAROL                  | 2300                           | GY3W            | L3-VE                       | 02/5～07/12  |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 |             |      |
|                                | 660                            | HB97S           | R06D                        | 21/12～      |           | 3.1   | 2.48      | 0.70        | 0.99 | 1.49 | ハイブリッド      |      |
|                                | 660                            | HB37S           | R06A                        | 21/12～      |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 |             |      |
|                                |                                |                 |                             |             |           | 3     | 2.4       | 0.68        | 0.96 | 1.44 | MT          |      |
|                                | 660                            | HB36S           | R06A                        | 15/1～21/11  |           | 3.2   | 2.56      | 0.72        | 1.02 | 1.54 | CVT         |      |
|                                |                                |                 |                             |             |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 |             |      |
|                                | 660                            | HB35S           | R06A                        | 12/11～14/11 |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 |             |      |
|                                | 660                            | HB25S           | K6A(DOHC)                   | 09/12～14/11 |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 | 3.0-3.3     |      |
| スクラム<br>SCRUM                  | 660                            | DG17V.DG17W     | R06A(TURBO)                 | 22/4～       |           | 3     | 2.4       | 0.68        | 0.96 | 1.44 | MT          |      |
|                                |                                |                 |                             |             |           | 3.2   | 2.56      | 0.72        | 1.02 | 1.54 | CVT         |      |
|                                | 660                            | HB24S           | K6A(DOHC)                   | 04/9～09/11  |           | 3     | 2.4       | 0.68        | 0.96 | 1.44 | MT          |      |
|                                |                                |                 |                             |             |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 | AT          |      |
|                                | 660                            | DG17V.DG17W     | R06A(TURBO)                 | 15/2～22/3   |           | 5.5   | 4.4       | 1.24        | 1.76 | 2.64 | MT          |      |
|                                |                                |                 |                             |             |           | 5.4   | 4.32      | 1.22        | 1.73 | 2.59 | AT          |      |
|                                | 660                            | DG17V           | R06A(NA)                    | 22/4～       |           | 5.4   | 4.32      | 1.22        | 1.73 | 2.59 | MT/AGS      |      |
|                                |                                |                 |                             |             |           | 5.2   | 4.16      | 1.17        | 1.66 | 2.50 | AT          |      |
| スクラムトラッ<br>ク<br>SCRUM<br>TRUCK | 660                            | DG17V.DG17W     | R06A(TURBO)                 | 15/2～22/3   |           | 5.4   | 4.32      | 1.22        | 1.73 | 2.59 |             |      |
|                                |                                |                 |                             |             |           | 5.5   | 4.4       | 1.24        | 1.76 | 2.64 | MT/AGS      |      |
|                                | 660                            | DG17V           | R06A(NA)                    | 15/2～22/3   |           | 5.3   | 4.24      | 1.19        | 1.70 | 2.54 | AT          |      |
|                                |                                |                 |                             |             |           | 6     | 4.8       | 1.35        | 1.92 | 2.88 | MT          |      |
|                                | 660                            | DG64V.DG64W     | K6A(DOHC,TURBO)             | 05/9～15/1   |           | 6.2   | 4.96      | 1.40        | 1.98 | 2.98 | AT          |      |
|                                |                                |                 |                             |             |           | 5.9   | 4.72      | 1.33        | 1.89 | 2.83 | MT          |      |
|                                | 660                            | DG64V.DG64W     | K6A(DOHC)                   | 05/9～15/1   |           | 5.8   | 4.64      | 1.31        | 1.86 | 2.78 | AT          |      |
|                                |                                |                 |                             |             |           | 2.8   | 2.24      | 0.63        | 0.90 | 1.34 |             |      |
|                                | 660                            | DG62V.DG62W     | K6A(DOHC,TURBO)             | 01/9～05/8   |           | 2.8   | 2.24      | 0.63        | 0.90 | 1.34 |             |      |
|                                |                                |                 |                             |             |           | 3.6   | 2.88      | 0.81        | 1.15 | 1.73 | MT          |      |
| スピアーノ<br>SPIANO                | 660                            | HF21S           | K6A(DOHC,TURBO)             | 02/10～      |           | 3.9   | 3.12      | 0.88        | 1.25 | 1.87 | AT          |      |
|                                |                                |                 |                             |             |           | 4.1   | 3.28      | 0.92        | 1.31 | 1.97 | MT          |      |
|                                | 660                            | DG63T           | K6A(DOHC)                   | 01/9～13/8   |           | 4.4   | 3.52      | 0.99        | 1.41 | 2.11 | AT          |      |
|                                |                                |                 |                             |             |           | 3.2   | 2.56      | 0.72        | 1.02 | 1.54 | MT          |      |
| デミオ<br>DEMIO                   | 660                            | HF21S           | K6A(DOHC)                   | 02/1～       |           | 3.5   | 2.8       | 0.79        | 1.12 | 1.68 | AT          |      |
|                                |                                |                 |                             |             |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 |             |      |
|                                | 1500                           | DJLFS           | P5-VPS                      | 15/10～19/8  |           | 5     | 4         | 1.13        | 1.60 | 2.40 |             |      |
|                                |                                |                 |                             |             |           | 5     | 4         | 1.13        | 1.60 | 2.40 | MT          |      |
|                                | 1300                           | DJ3FS.DJ3AS     | P3-VPS                      | 14/9～19/8   |           | 5.2   | 4.16      | 1.17        | 1.66 | 2.50 | AT          |      |
|                                |                                |                 |                             |             |           | 6.6   | 5.28      | 1.49        | 2.11 | 3.17 | MT          |      |
|                                | 1500                           | DJ5FS.DJ5AS     | S5-DPTS,S5-DPTR(SKYACTIV-D) | 14/10～19/8  |           | 6.8   | 5.44      | 1.53        | 2.18 | 3.26 | AT          |      |
|                                |                                |                 |                             |             |           | 2     | 1.6       | 0.45        | 0.64 | 0.96 | インタークーラー    |      |
|                                | 1300                           | DEJFS           | P3-VPS(SKYACTIV)            | 12/5～14/8   |           | 6.1   | 4.88      | 1.37        | 1.95 | 2.93 |             |      |
|                                |                                |                 |                             |             |           | 5.3   | 4.24      | 1.19        | 1.70 | 2.54 | MT          |      |
| ピアンテ<br>BIANTE                 | 1300                           | DE3FS.DE3AS     | ZJ-VE                       | 07/7～14/8   |           | 5     | 4         | 1.13        | 1.60 | 2.40 | AT          |      |
|                                |                                |                 |                             |             |           | 5.5   | 4.4       | 1.24        | 1.76 | 2.64 | CVT         |      |
|                                | 1500                           | DE5FS           | ZY-VE                       | 07/7～14/8   |           | 5.1   | 4.08      | 1.15        | 1.63 | 2.45 | MT          |      |
|                                |                                |                 |                             |             |           | 5.4   | 4.32      | 1.22        | 1.73 | 2.59 | CVT         |      |
|                                | 1300                           | DY3W            | ZJ-VE                       | 02/8～07/7   |           | 4.7   | 3.76      | 1.06        | 1.50 | 2.26 |             |      |
|                                |                                |                 |                             |             |           | 4.7   | 3.76      | 1.06        | 1.50 | 2.26 |             |      |
|                                | 2000                           | CCFFW           | PE-VPS(SKYACTIV)            | 13/5～       |           | 8.9   | 7.12      | 2.00        | 2.85 | 4.27 |             |      |
|                                |                                |                 |                             |             |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 | リアヒーター無し    |      |
|                                | 2000                           | CCEFW           | LF-VDS                      | 09/6～13/4   |           | 8.3   | 6.64      | 1.87        | 2.66 | 3.98 | リアヒーター      |      |
|                                |                                |                 |                             |             |           | 7.7   | 6.16      | 1.73        | 2.46 | 3.70 | リアヒーター無し    |      |
| ファミリアバン<br>FAMILIA VAN         | 2300                           | CC3FW           | L3-VE                       | 08/7～13/4   |           | 8.4   | 6.72      | 1.89        | 2.69 | 4.03 | リアヒーター      |      |
|                                |                                |                 |                             |             |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 | リアヒーター無し    |      |
|                                | 2000                           | CCEFW.CCEAW     | LF-VD                       | 08/7～       |           | 8.3   | 6.64      | 1.87        | 2.66 | 3.98 | リアヒーター      |      |
|                                |                                |                 |                             |             |           | 4.5   | 3.6       | 1.01        | 1.44 | 2.16 |             |      |
| フレア<br>FLAIR                   | 1500                           | NHP160M         | 1NZ-FXE(HYBRID)             | 22/3～       |           | 1.6   | 1.28      | 0.36        | 0.51 | 0.77 | インバータークーラント |      |
|                                | 1500                           | NCP160M.NCP165M | 1NZ-FE                      | 18/6～       |           | 5     | 4         | 1.13        | 1.60 | 2.40 |             |      |
|                                | 660                            | MJ95S           | R06D(NA,HYBRID)             | 19/12～      |           | 3.1   | 2.48      | 0.70        | 0.99 | 1.49 |             |      |
| アテンザ<br>WAGON                  | 2500                           | GJ5FW           | PY-RPR                      | 18/5～19/7   |           | 6.9   | 5.52      | 1.55        | 2.21 | 3.31 |             |      |
|                                | 2000                           | GJEFW           | PE-VPR                      | 12/11～19/7  |           | 6.8   | 5.44      | 1.53        | 2.18 | 3.26 |             |      |
|                                | 2200                           | GJ2FW.GJ2AW     | SH-VPTR(SKYACTIV-D)         | 12/11～18/4  |           | 8.8   | 7.04      | 1.98        | 2.82 | 4.22 | MT          |      |
|                                |                                |                 |                             |             |           | 9.1   | 7.28      | 2.05        | 2.91 | 4.37 | AT          |      |
|                                | 2500                           | GJ5FW           | PY-VPR                      | 12/11～18/4  |           | 6.9   | 5.52      | 1.55        | 2.21 | 3.31 |             |      |
| キャロル<br>CAROL                  | 2000                           | GHEFW           | LF-VD                       | 10/1～12/11  |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 |             |      |
|                                | 2500                           | GH5FW.GH5AW     | L5-VE                       | 08/1～12/11  |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 |             |      |
|                                | 2000                           | GHEFW           | LF-VE                       | 08/1～10/1   |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 |             |      |
|                                | 2000                           | GYEW            | LF-DE                       | 02/5～07/12  |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 |             |      |
|                                | 2300                           | GY3W            | L3-VE                       | 02/5～07/12  |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 |             |      |
|                                | 660                            | HB97S           | R06D                        | 21/12～      |           | 3.1   | 2.48      | 0.70        | 0.99 | 1.49 | ハイブリッド      |      |
|                                | 660                            | HB37S           | R06A                        | 21/12～      |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 |             |      |
|                                |                                |                 |                             |             |           | 3     | 2.4       | 0.68        | 0.96 | 1.44 | MT          |      |
| スクラム<br>SCRUM                  | 660                            | DG17V.DG17W     | R06A(TURBO)                 | 22/4～       |           | 3.2   | 2.56      | 0.72        | 1.02 | 1.54 | CVT         |      |
|                                |                                |                 |                             |             |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 |             |      |
|                                | 660                            | HB35S           | R06A                        | 12/11～14/11 |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 |             |      |
|                                |                                |                 |                             |             | 660       | HB25S | K6A(DOHC) | 09/12～14/11 |      | 3.3  | 2.64        | 0.74 |
|                                | 660                            | HB24S           | K6A(DOHC)                   | 04/9～09/11  |           |       |           |             |      | 3    | 2.4         | 0.68 |
|                                |                                |                 |                             |             |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 | AT          |      |
|                                | スクラムトラッ<br>ク<br>SCRUM<br>TRUCK | 660             | DG17V.DG17W                 | R06A(TURBO) | 15/2～22/3 |       | 5.5       | 4.4         | 1.24 | 1.76 | 2.64        | MT   |
|                                |                                |                 |                             |             |           |       | 5.4       | 4.32        | 1.22 | 1.73 | 2.59        | AT   |
| 660                            |                                | DG17V           | R06A(NA)                    | 22/4～       |           | 5.4   | 4.32      | 1.22        | 1.73 | 2.59 | MT/AGS      |      |
|                                |                                |                 |                             |             |           | 5.2   | 4.16      | 1.17        | 1.66 | 2.50 | AT          |      |
| 660                            |                                | DG17V.DG17W     | R06A(TURBO)                 | 15/2～22/3   |           | 5.4   | 4.32      | 1.22        | 1.73 | 2.59 |             |      |
|                                |                                |                 |                             |             |           | 5.5   | 4.4       | 1.24        | 1.76 | 2.64 | MT/AGS      |      |
| 660                            |                                | DG17V           | R06A(NA)                    | 15/2～22/3   |           | 5.3   | 4.24      | 1.19        | 1.70 | 2.54 | AT          |      |
|                                |                                |                 |                             |             |           | 6     | 4.8       | 1.35        | 1.92 | 2.88 | MT          |      |
| スピアーノ<br>SPIANO                | 660                            | DG64V.DG64W     | K6A(DOHC,TURBO)             | 05/9～15/1   |           | 6.2   | 4.96      | 1.40        | 1.98 | 2.98 | AT          |      |
|                                |                                |                 |                             |             |           | 5.9   | 4.72      | 1.33        | 1.89 | 2.83 | MT          |      |
|                                | 660                            | DG64V.DG64W     | K6A(DOHC)                   | 05/9～15/1   |           | 5.8   | 4.64      | 1.31        | 1.86 | 2.78 | AT          |      |
|                                |                                |                 |                             |             |           | 2.8   | 2.24      | 0.63        | 0.90 | 1.34 |             |      |
|                                | 660                            | DG62V.DG62W     | K6A(DOHC,TURBO)             | 01/9～05/8   |           | 2.8   | 2.24      | 0.63        | 0.90 | 1.34 |             |      |
|                                |                                |                 |                             |             |           | 3.6   | 2.88      | 0.81        | 1.15 | 1.73 | MT          |      |
|                                | 660                            | DG16T           | R06A(NA)                    | 13/9～       |           | 3.9   | 3.12      | 0.88        | 1.25 | 1.87 | AT          |      |
|                                |                                |                 |                             |             |           | 4.1   | 3.28      | 0.92        | 1.31 | 1.97 | MT          |      |
|                                | デミオ<br>DEMIO                   | 660             | DG63T                       | K6A(DOHC)   | 01/9～13/8 |       | 4.4       | 3.52        | 0.99 | 1.41 | 2.11        | AT   |
|                                |                                |                 |                             |             |           |       | 3.2       | 2.56        | 0.72 | 1.02 | 1.54        | MT   |
| 660                            |                                | HF21S           | K6A(DOHC,TURBO)             | 02/10～      |           | 3.5   | 2.8       | 0.79        | 1.12 | 1.68 | AT          |      |
|                                |                                |                 |                             |             |           | 3.3   | 2.64      | 0.74        | 1.06 | 1.58 |             |      |
| ファミリアバン<br>FAMILIA VAN         | 1500                           | DJLFS           | P5-VPS                      | 15/10～19/8  |           | 5     | 4         | 1.13        | 1.60 | 2.40 |             |      |
|                                |                                |                 |                             |             |           | 5     | 4         | 1.13        | 1.60 | 2.40 | MT          |      |
|                                | 1300                           | DJ3FS.DJ3AS     | P3-VPS                      | 14/9～19/8   |           | 5.2   | 4.16      | 1.17        | 1.66 | 2.50 | AT          |      |
|                                |                                |                 |                             |             |           | 6.6   | 5.28      | 1.49        | 2.11 | 3.17 | MT          |      |
|                                | 1500                           | DJ5FS.DJ5AS     | S5-DPTS,S5-DPTR(SKYACTIV-D) | 14/10～19/8  |           | 6.8   | 5.44      | 1.53        | 2.18 | 3.26 | AT          |      |
|                                |                                |                 |                             |             |           | 2     | 1.6       | 0.45        | 0.64 | 0.96 | インタークーラー    |      |
|                                | 1300                           | DEJFS           | P3-VPS(SKYACTIV)            | 12/5～14/8   |           | 6.1   | 4.88      | 1.37        | 1.95 | 2.93 |             |      |
|                                |                                |                 |                             |             |           | 5.3   | 4.24      | 1.19        | 1.70 | 2.54 | MT          |      |
|                                | ピアンテ<br>BIANTE                 | 1300            | DE3FS.DE3AS                 | ZJ-VE       | 07/7～14/8 |       | 5         | 4           | 1.13 | 1.60 | 2.40        | AT   |
|                                |                                |                 |                             |             |           |       | 5.5       | 4.4         | 1.24 | 1.76 | 2.64        | CVT  |
| 1500                           |                                | DE5FS           | ZY-VE                       | 07/7～14/8   |           | 5.1   | 4.08      | 1.15        | 1.63 | 2.45 | MT          |      |
|                                |                                |                 |                             |             |           | 5.4   | 4.32      | 1.22        | 1.73 | 2.59 | CVT         |      |
| 1300                           |                                | DY3W            | ZJ-VE                       | 02/8～07/7   |           | 4.7   | 3.76      | 1.06        | 1.50 | 2.26 |             |      |
|                                |                                |                 |                             |             |           | 4.7   | 3.76      | 1.06        | 1.50 | 2.26 |             |      |
| 2000                           |                                | CCFFW           | PE-VPS(SKYACTIV)            | 13/5～       |           | 8.9   | 7.12      | 2.00        | 2.85 | 4.27 |             |      |
|                                |                                |                 |                             |             |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 | リアヒーター無し    |      |
| ファミリアバン<br>FAMILIA VAN         | 2000                           | CCEFW           | LF-VDS                      | 09/6～13/4   |           | 8.3   | 6.64      | 1.87        | 2.66 | 3.98 | リアヒーター      |      |
|                                |                                |                 |                             |             |           | 7.7   | 6.16      | 1.73        | 2.46 | 3.70 | リアヒーター無し    |      |
|                                | 2300                           | CC3FW           | L3-VE                       | 08/7～13/4   |           | 8.4   | 6.72      | 1.89        | 2.69 | 4.03 | リアヒーター      |      |
|                                |                                |                 |                             |             |           | 7.5   | 6         | 1.69        | 2.40 | 3.60 | リアヒーター無し    |      |
| フレア<br>FLAIR                   | 2000                           | CCEFW.CCEAW     | LF-VD                       | 08/7～       |           | 8.3   | 6.64      | 1.87        | 2.66 | 3.98 | リアヒーター      |      |
|                                |                                |                 |                             |             |           | 4.5   | 3.6       | 1.01        | 1.44 | 2.16 |             |      |
|                                | 1500                           | NHP160M         | 1NZ-FXE(HYBRID)             | 22/3～       |           | 1.6   | 1.28      | 0.36        | 0.51 | 0.77 | インバータークーラント |      |
| アテンザ<br>WAGON                  | 1500                           | NCP160M.NCP165M | 1NZ-FE                      | 18/6～       |           | 5     | 4         | 1.13        | 1.60 | 2.40 |             |      |
|                                | 660                            | MJ95S           | R06D(NA,HYBRID)             | 19/12～      |           | 3.1   | 2.48      | 0.70        | 0.99 | 1.49 |             |      |
|                                | 660                            | MJ55S           | R06A(NA,HYBRID)             | 17/3～19/11  |           | 3.1   | 2.48      | 0.70        | 0.99 | 1.49 |             |      |
|                                | 660                            | MJ44S           | R06A(TURBO)                 | 15/8～17/1   |           | 3.4   | 2.72      | 0.77        | 1.09 | 1.63 |             |      |
|                                | 660                            | MJ44S           | R06A(NA)                    | 14/8～17/1   |           | 2.9   | 2.32      | 0.65        | 0.93 | 1.39 | MT          |      |
|                                |                                |                 |                             |             | 3.2       | 2.56  | 0.72      | 1.02        | 1.54 | CVT  |             |      |
| アテンザ<br>WAGON                  | 660                            | MJ34S           | R06A(TURBO)                 | 12/10～17/1  |           | 3.4   | 2.72      | 0.77        | 1.09 | 1.63 |             |      |
|                                | 2200                           | GJ2FW.GJ2AW     | SH-VPTR(SKYACTIV-D)         | 18/5～19/7   |           | 8.6   | 6.88      | 1.94        | 2.   |      |             |      |

|                                         |      |             |                  |             |     |      |      |      |      |      |
|-----------------------------------------|------|-------------|------------------|-------------|-----|------|------|------|------|------|
|                                         | 660  | MJ34S       | R06A(NA)         | 12/10～17/1  | 2.9 | 2.32 | 0.65 | 0.93 | 1.39 | MT   |
|                                         |      |             |                  |             | 3.2 | 2.56 | 0.72 | 1.02 | 1.54 | CVT  |
| フレアクロス<br>オーバー<br>FLAIR<br>CROSSOVER    | 660  | MS52S       | R06A(TURBO)      | 20/2～       | 3.1 | 2.48 | 0.70 | 0.99 | 1.49 |      |
|                                         | 660  | MS92S       | R06D(NA)         | 20/2～       | 3.1 | 2.48 | 0.70 | 0.99 | 1.49 |      |
|                                         | 660  | MS41S       | R06A(TURBO)      | 15/12～19/12 | 3.4 | 2.72 | 0.77 | 1.09 | 1.63 |      |
|                                         | 660  | MS41S       | R06A(NA)         | 15/5～19/12  | 3.2 | 2.56 | 0.72 | 1.02 | 1.54 |      |
|                                         | 660  | MS31S       | R06A(TURBO)      | 14/1～19/12  | 3.4 | 2.72 | 0.77 | 1.09 | 1.63 |      |
|                                         | 660  | MS31S       | R06A(NA)         | 14/1～15/4   | 3   | 2.4  | 0.68 | 0.96 | 1.44 |      |
| フレアワゴン<br>FLAIR WAGON                   | 660  | MM54S       | R06A(TURBO)      | 23/12～      | 3.2 | 2.56 | 0.72 | 1.02 | 1.54 |      |
|                                         | 660  | MM94S       | R06D(NA)         | 23/12～      | 3.1 | 2.48 | 0.70 | 0.99 | 1.49 |      |
|                                         | 660  | MM53S       | R06A(TURBO)      | 18/2～23/11  | 3.1 | 2.48 | 0.70 | 0.99 | 1.49 |      |
|                                         | 660  | MM53S       | R06A(NA)         | 18/2～23/11  | 3.3 | 2.64 | 0.74 | 1.06 | 1.58 |      |
|                                         | 660  | MM42S       | R06A(TURBO)      | 15/8～18/1   | 3.2 | 2.56 | 0.72 | 1.02 | 1.54 |      |
|                                         | 660  | MM42S       | R06A(NA)         | 15/5～18/1   | 3.2 | 2.56 | 0.72 | 1.02 | 1.54 |      |
|                                         | 660  | MM32S       | R06A(TURBO)      | 13/4～15/5   | 3.2 | 2.56 | 0.72 | 1.02 | 1.54 |      |
|                                         | 660  | MM32S       | R06A(NA)         | 13/4～18/1   | 3.2 | 2.56 | 0.72 | 1.02 | 1.54 |      |
|                                         | 660  | MM21S       | K6A(TURBO)       | 12/6～13/3   | 3.4 | 2.72 | 0.77 | 1.09 | 1.63 |      |
|                                         | 660  | MM21S       | K6A(DOHC)        | 12/6～13/3   | 3.2 | 2.56 | 0.72 | 1.02 | 1.54 |      |
| プレマシー<br>PREMACY                        | 2000 | CWFFW       | PE-VPS(SKYACTIV) | 13/1～18/3   | 6.6 | 5.28 | 1.49 | 2.11 | 3.17 |      |
|                                         | 2000 | CWEFW       | LF-VDS           | 10/7～12/12  | 6   | 4.8  | 1.35 | 1.92 | 2.88 |      |
|                                         | 2000 | CWEFW       | LF-VD            | 10/7～18/3   | 6   | 4.8  | 1.35 | 1.92 | 2.88 |      |
|                                         | 2000 | CWEAW       | LF-VE            | 10/7～18/3   | 6   | 4.8  | 1.35 | 1.92 | 2.88 |      |
|                                         | 2000 | CREW        | LF-VD(DISI)      | 07/1～10/6   | 7.5 | 6    | 1.69 | 2.40 | 3.60 |      |
|                                         | 2000 | CREW        | LF-DE            | 05/2～10/6   | 7.5 | 6    | 1.69 | 2.40 | 3.60 |      |
|                                         | 2300 | CR3W        | L3-VE            | 05/2～10/6   | 7.5 | 6    | 1.69 | 2.40 | 3.60 |      |
|                                         | 2000 | CPEW        | FS-ZE(DOHC)      | 02/11～05/1  | 7.5 | 6    | 1.69 | 2.40 | 3.60 |      |
|                                         | 2000 | CPEW        | FS-DE(DOHC)      | 01/7～02/11  | 7.5 | 6    | 1.69 | 2.40 | 3.60 |      |
|                                         | 1800 | CP8W        | FP-DE(DOHC)      | 99/3～05/1   | 7.5 | 6    | 1.69 | 2.40 | 3.60 |      |
| ベリーサ<br>VERISA                          | 1500 | DC5W        | ZY-VE            | 04/6～06/8   | 5   | 4    | 1.13 | 1.60 | 2.40 |      |
|                                         | 1500 | DC5R        | ZY-VE            | 04/6～06/8   | 5.5 | 4.4  | 1.24 | 1.76 | 2.64 |      |
| ボンゴトラック<br>BONGO<br>TRUCK               | 1800 | SLP2T,SLP2L | L8               | 16/2～       | 7.4 | 5.92 | 1.67 | 2.37 | 3.55 | MT   |
|                                         |      |             |                  |             | 7.8 | 6.24 | 1.76 | 2.50 | 3.74 | AT   |
| ボンゴバン<br>BONGO VAN                      | 1800 | SLP2V,SLP2M | L8               | 16/2～       | 7.4 | 5.92 | 1.67 | 2.37 | 3.55 | MT   |
|                                         |      |             |                  |             | 7.8 | 6.24 | 1.76 | 2.50 | 3.74 | AT   |
| マツダスピード<br>アクセラ<br>MAZDASPEED<br>AXELA  | 2300 | BL3FW       | L3-VDT(TURBO)    | 09/6～13/11  | 7.5 | 6    | 1.69 | 2.40 | 3.60 |      |
|                                         | 2300 | BK3P        | L3-VDT(TURBO)    | 06/6～09/6   | 7.5 | 6    | 1.69 | 2.40 | 3.60 |      |
| マツダスピード<br>アテンザ<br>MAZDASPEED<br>ATENZA | 2300 | GG3P        | L3-VDT(TURBO)    | 05/6～07/12  | 8   | 6.4  | 1.80 | 2.56 | 3.84 |      |
| ラピュタ<br>LAPUTA                          | 660  | HP22S       | K6A(DOHC,VVT)    | 01/4～05/12  | 3.2 | 2.56 | 0.72 | 1.02 | 1.54 | MT   |
|                                         |      |             |                  |             | 0.5 | 0.4  | 0.11 | 0.16 | 0.24 | AT   |
|                                         | 660  | HP22S       | K6A(DOHC,TURBO)  | 01/4～05/12  | 3   | 2.4  | 0.68 | 0.96 | 1.44 | MT   |
|                                         |      |             |                  |             | 3.3 | 2.64 | 0.74 | 1.06 | 1.58 | AT   |
|                                         | 660  | HP12S       | F6A(TURBO)       | 01/4～05/12  | 3.4 | 2.72 | 0.77 | 1.09 | 1.63 | MT   |
|                                         |      |             |                  |             | 3.7 | 2.96 | 0.83 | 1.18 | 1.78 | AT   |
| ロードスター<br>ROADSTER                      | 1500 | ND5RE       | P5-VP,P5-VPR     | 24/1～       | 6.2 | 4.96 | 1.40 | 1.98 | 2.98 | MT   |
|                                         |      |             |                  |             | 5.6 | 4.48 | 1.26 | 1.79 | 2.69 | AT   |
|                                         | 1500 | ND5RC       | P5-VP,P5-VPR     | 15/5～23/12  | 5.8 | 4.64 | 1.31 | 1.86 | 2.78 | MT   |
|                                         |      |             |                  |             | 5.6 | 4.48 | 1.26 | 1.79 | 2.69 | AT   |
|                                         |      |             |                  |             | 6.2 | 4.96 | 1.40 | 1.98 | 2.98 | NR-A |
|                                         | 2000 | NCEC        | LF-VE            | 08/12～15/5  | 7.7 | 6.16 | 1.73 | 2.46 | 3.70 | MT   |
|                                         |      |             |                  |             | 7   | 5.6  | 1.58 | 2.24 | 3.36 | AT   |
|                                         | 2000 | NCEC        | LF-VE            | 05/8～08/11  | 7.5 | 6    | 1.69 | 2.40 | 3.60 |      |
|                                         | 1600 | NB6C        | B6-ZE(DOHC)      | 98/1～05/7   | 6   | 4.8  | 1.35 | 1.92 | 2.88 |      |
|                                         | 1800 | NB8C        | BP-ZE(DOHC)      | 98/1～05/7   | 6   | 4.8  | 1.35 | 1.92 | 2.88 |      |
|                                         | 1800 | NA8C        | BP-ZE(DOHC)      | 95/8～98/1   | 6   | 4.8  | 1.35 | 1.92 | 2.88 |      |
|                                         |      |             |                  | 93/9～95/7   | 10  | 8    | 2.25 | 3.20 | 4.80 |      |
|                                         | 1600 | NA6CE       | B6(DOHC)         | 89/9～98/1   | 6   | 4.8  | 1.35 | 1.92 | 2.88 |      |
| ロードスター<br>RF<br>ROADSTER RF             | 2000 | NDERE       | PE-VPR           | 24/1～       | 6.2 | 4.96 | 1.40 | 1.98 | 2.98 | MT   |
|                                         |      |             |                  |             | 5.8 | 4.64 | 1.31 | 1.86 | 2.78 | AT   |
|                                         | 2000 | NDERC       | PE-VPR           | 16/12～23/12 | 6.2 | 4.96 | 1.40 | 1.98 | 2.98 | MT   |
|                                         |      |             |                  |             | 6   | 4.8  | 1.35 | 1.92 | 2.88 | AT   |