

DAIHATSU

※実車上で交換可能なクーラント量は全容量の80％程度となります。

車両	排気量	車両型式	エンジン	年式	冷却水全量A	Aの80%量	31%(-15度)に なる抜量	全交換40% クーラント量	全交換40%の水量	備考
YRV	1300	M201G.M211G	K3VET(DOHC,VVT,TURBO)	00/8～05/8	5.2	4.16	1.17	1.66	2.50	
	1300	M201G.M211G	K3VE(DOHC,VVT)	00/8～05/8	5	4	1.13	1.60	2.40	
アトレー ATRAI	660	S700V.S710V	KE-VET	21/12～	5.7	4.56	1.28	1.82	2.74	リアヒーター無し
					6.1	4.88	1.37	1.95	2.93	リアヒーター
	660	S700W.S710W	KF-VET	21/12～	5.7	4.56	1.28	1.82	2.74	リアヒーター無し
					6.1	4.88	1.37	1.95	2.93	リアヒーター
アトレーワゴン ATRAI WAGON	660	S321G.S331G	KF-DET(DOHC,TURBO)	07/9～21/11	5.8	4.64	1.31	1.86	2.78	
	660	S320G.S330G	EF-DET(DOHC,TURBO)	05/5～07/9	6.4	5.12	1.44	2.05	3.07	MT
					6.3	5.04	1.42	2.02	3.02	AT
					5.5	4.4	1.24	1.76	2.64	MT
	660	S220G.S230G	EF-DET(DOHC,TURBO)	01/12～05/4	5.4	4.32	1.22	1.73	2.59	AT
					5.5	4.4	1.24	1.76	2.64	MT
アルティス ALTIS	2500	AXVH70N	A25A-FXS(HYBRID)	17/7～23/12	5.3	4.24	1.19	1.70	2.54	AT
					6.1	4.88	1.37	1.95	2.93	
	2500	AVV50N	2AR-FXE	12/5～17/6	1.7	1.36	0.38	0.54	0.82	パワーコントロールユニット のクーラント
					7.2	5.76	1.62	2.30	3.46	
	2400	ACV40N.AC45N	2AZ-FE	06/1～10/2	3.2	2.56	0.72	1.02	1.54	インバータークーラント
					6.2	4.96	1.40	1.98	2.98	
	2400	ACV30N.SXV35N	2AZ-FE	01/9～06/1	6.2	4.96	1.40	1.98	2.98	
					6.2	4.96	1.40	1.98	2.98	
ウェイク WAKE	660	LA700S.LA710S	KF-VE	14/11～22/9	3.5	2.8	0.79	1.12	1.68	
	660	LA700S.LA710S	KF-VET(TURBO)	14/11～22/9	3.5	2.8	0.79	1.12	1.68	
エッセ ESSE	660	L235S.L245S	KF-VE	05/12～11/9	3.5	2.8	0.79	1.12	1.68	
キャスト CAST	660	LA250S.LA260S	KF-VE	15/9～23/8	3.4	2.72	0.77	1.09	1.63	
	660	LA250S.LA260S	KF-VET(TURBO)	15/9～23/8	3.5	2.8	0.79	1.12	1.68	
クー COO	1300	M401S.M411S	K3-VE	06/5～13/1	4.2	3.36	0.95	1.34	2.02	
	1500	M402S	3SZ-VE	06/5～13/1	4.4	3.52	0.99	1.41	2.11	
コペン COPEN	660	LA400K	KF-VET(TURBO)	14/6～	3	2.4	0.68	0.96	1.44	
	660	L880K	JB-DET(TURBO)	02/6～12/9	3.8	3.04	0.86	1.22	1.82	
ソニカ SONICA	660	L405S.L415S	KF-DET(DOHC,TURBO)	06/6～09/5	3.6	2.88	0.81	1.15	1.73	
タント TANTO	660	LA650S.LA660S	KF-VE	19/7～	3.4	2.72	0.77	1.09	1.63	
	660	LA650S.LA660S	KF-VET(TURBO)	19/7～	3.4	2.72	0.77	1.09	1.63	
	660	LA600S.LA610S	KF-VE	13/10～19/6	3.5	2.8	0.79	1.12	1.68	
	660	LA600S.LA610S	KF-VET(TURBO)	13/10～19/6	3.5	2.8	0.79	1.12	1.68	
	660	L375S.L385S	KF-VE	07/12～13/9	3	2.4	0.68	0.96	1.44	
	660	L375S.L385S	KF-DET(DOHC,TURBO)	07/12～13/9	3.2	2.56	0.72	1.02	1.54	
	660	L350S.L360S	EF-DET(DOHC・TURBO)	03/11～07/12	3.4	2.72	0.77	1.09	1.63	
	660	L350S.L360S	EF-VE(DOHC)	03/11～07/12	3.3	2.64	0.74	1.06	1.58	
タントエグゼ TANTO EXE	660	L455S.L465S	KF-VE	09/12～	2.8	2.24	0.63	0.90	1.34	
	660	L455S.L465S	KF-VET(TURBO)	09/12～	3.1	2.48	0.70	0.99	1.49	
トール THOR	1000	M900S.M910S	1KR-FE	16/11～	4.4	3.52	0.99	1.41	2.11	
	1000	M900S	1KR-VET	16/11～	5	4	1.13	1.60	2.40	
ハイゼットカーゴ HIJET CARGO	660	S700V.S710V	KF-VE	21/12～	5.7	4.56	1.28	1.82	2.74	リアヒーター無し
					5.8	4.64	1.31	1.86	2.78	リアヒーター
	660	S700V.S710V	KE-VET	21/12～	5.7	4.56	1.28	1.82	2.74	リアヒーター無し
					6.1	4.88	1.37	1.95	2.93	リアヒーター
	660	S700W.S710W	KF-VE	21/12～	5.4	4.32	1.22	1.73	2.59	MT
					5.6	4.48	1.26	1.79	2.69	CVT
	660	S321V.S331V	KF-VE	07/12～21/11	5.7	4.56	1.28	1.82	2.74	MT
					5.6	4.48	1.26	1.79	2.69	AT
	660	S321V.S331V	KF-DET(DOHC,TURBO)	07/12～21/11	5.9	4.72	1.33	1.89	2.83	MT
					5.8	4.64	1.31	1.86	2.78	AT
	660	S320V.S330V.S320W.S330W	EF-SE	04/12～07/11	6.4	5.12	1.44	2.05	3.07	MT
					6.2	4.96	1.40	1.98	2.98	AT
ハイゼットトラック HIJET TRUCK	660	S320V.S330V	EF-DET(DOHC,TURBO)	04/12～07/11	6.4	5.12	1.44	2.05	3.07	MT
					6.3	5.04	1.42	2.02	3.02	AT
	660	S500P.S510P	KF-VE	14/9～	3.8	3.04	0.86	1.22	1.82	
	660	S201P.S211P	KF-VE	07/12～14/8	3.8	3.04	0.86	1.22	1.82	
					5	4	1.13	1.60	2.40	MT
	660	S200P.S210P	EF-SE	04/12～07/11	4.8	3.84	1.08	1.54	2.30	AT
					5.5	4.4	1.24	1.76	2.64	MT
	660	S200P.S210P	EF-VE(DOHC)	04/12～07/11	5.3	4.24	1.19	1.70	2.54	AT
ブーン BOON	1000	M700S.M710S	1KR-FE	16/4～	4.3	3.44	0.97	1.38	2.06	
	1300	M601S	1NR-FE	10/2～12/5	4.5	3.6	1.01	1.44	2.16	
	1000	M600S.M610S	1KR-FE	10/2～16/3	4.3	3.44	0.97	1.38	2.06	
	940	M312S	KJ-VET	06/3～10/1	3.5	2.8	0.79	1.12	1.68	
	1300	M301S	K3-VE	05/1～10/1	4.1	3.28	0.92	1.31	1.97	
	1000	M300S.M310S	1KR-FE	04/6～10/1	3.9	3.12	0.88	1.25	1.87	
ブーンルミナス BOON Luminas	1500	M502G.M512G	3SZ-VE	08/12～12/3	4.5	3.6	1.01	1.44	2.16	
マックス MAX	660	L952S.L962S	JB-DET(TURBO)	02/5～05/12	3.6	2.88	0.81	1.15	1.73	
	660	L950S.L960S	EF-DET(DOHC,TURBO)	01/10～05/12	3.5	2.8	0.79	1.12	1.68	MT
					3.4	2.72	0.77	1.09	1.63	AT
	660	L950S	EF-VE(DOHC)	01/10～05/12	3.4	2.72	0.77	1.09	1.63	
	660	L960S	EF-VF(DOHC)	01/10～05/12	3.4	2.72	0.77	1.09	1.63	MT

						3.3	2.64	0.74	1.06	1.58	AT
ミラノ/カスタム MIRA/CUSTOM	660	L275S.L285S	KF-DET(DOHC,TURBO)	06/12～		3	2.4	0.68	0.96	1.44	
	660	L275S.L285S	KF-VE	06/12～		3.1	2.48	0.70	0.99	1.49	MT
						3	2.4	0.68	0.96	1.44	CVT
	660	L250S.L260S	EF-DET	02/12～06/12		3.5	2.8	0.79	1.12	1.68	MT
						3.4	2.72	0.77	1.09	1.63	AT
	660	L250S.L260S	EF(NA)	02/12～06/12		3.6	2.88	0.81	1.15	1.73	MT
					3.5	2.8	0.79	1.12	1.68	AT	
					3.4	2.72	0.77	1.09	1.63	CVT	
ミラアヴィ MIRA AVY	660	L250S.S260S	EF-DET(DOHC・TURBO)	02/12～06/12		3.5	2.8	0.79	1.12	1.68	MT
						3.4	2.72	0.77	1.09	1.63	AT
	660	L250S.S260S	EF(NA)	02/12～06/12		3.6	2.88	0.81	1.15	1.73	MT
						3.5	2.8	0.79	1.12	1.68	AT
						3.4	2.72	0.77	1.09	1.63	CVT
ミライース MIRA eS	660	LA350S.LA360S	KF-VE	17/5～		2.9	2.32	0.65	0.93	1.39	
	660	LA300S.LA310S	KF-VE	11/9～17/4		3.2	2.56	0.72	1.02	1.54	
ミラココア MIRA COCOA	660	L675S.L685S	KF-VE	09/8～		3.2	2.56	0.72	1.02	1.54	
ミラジーノ MIRA GINO	660	L650S.L660S	EF-VE(DOHC)	04/11～09/4		3.3	2.64	0.74	1.06	1.58	
ミラトコット MIRA TOCOT	660	LA550S.LA560S	KF-VE	18/6～		3.2	2.56	0.72	1.02	1.54	
ミラバン MIRA VAN	660	L275V.L285V	KF-VE	06/12～		3.1	2.48	0.70	0.99	1.49	MT
						3	2.4	0.68	0.96	1.44	CVT
	660	L250V.L260V	EF(NA)	02/12～06/12		3.6	2.88	0.81	1.15	1.73	MT
						3.5	2.8	0.79	1.12	1.68	AT
ムーヴ/カスタム MOVE/CUSTOM	660	LA150S.LA160S	KF-VE	14/12～		3.4	2.72	0.77	1.09	1.63	
	660	LA150S.LA160S	KF-VET(DOHC,TURBO)	14/12～		3.5	2.8	0.79	1.12	1.68	
	660	LA100S.LA110S	KF-VE	10/12～14/11		2.8	2.24	0.63	0.90	1.34	
	660	LA100S.LA110S	KF-DET(DOHC,TURBO)	10/12～14/11		2.9	2.32	0.65	0.93	1.39	
	660	L175S.L185S	KF-VE	06/10～10/12		3.1	2.48	0.70	0.99	1.49	MT
						3	2.4	0.68	0.96	1.44	AT/CVT
	660	L175S.L185S	KF-DET(DOHC,TURBO)	06/10～10/12		3.2	2.56	0.72	1.02	1.54	AT
						3.2	2.56	0.72	1.02	1.54	CVT
	660	L150S	EF-VE(DOHC)	02/10～06/9		3.4	2.72	0.77	1.09	1.63	MT
						3.3	2.64	0.74	1.06	1.58	AT
	660	L150S	EF-DET(DOHC・TURBO)	02/10～06/9		3.5	2.8	0.79	1.12	1.68	MT
						3.4	2.72	0.77	1.09	1.63	AT
660	L152S	JB-DET(TURBO)	02/10～06/9		3.6	2.88	0.81	1.15	1.73		
ムーヴキャンバス MOVE CANBUS	660	LA850S.LA860S	KF-VE	22/7～		3.4	2.72	0.77	1.09	1.63	
	660	LA850S.LA860S	KF-VET	22/7～		3.4	2.72	0.77	1.09	1.63	
	660	LA800S.LA810S	KF-VE	16/9～22/6		3.5	2.8	0.79	1.12	1.68	
ムーヴコンテ MOVE CONTE	660	L575S.L585S	KF-VE	08/8～16/12		3.3	2.64	0.74	1.06	1.58	
	660	L575S.L585S	KF-DET(DOHC,TURBO)	08/8～16/12		3	2.4	0.68	0.96	1.44	
ムーヴラテ MOVE LATTE	660	L550S.L560S	EF-VE(DOHC)	04/8～09/12		3.3	2.64	0.74	1.06	1.58	
	660	L550S.L560S	EF-DET(DOHC・TURBO)	04/8～09/12		3.4	2.72	0.77	1.09	1.63	
メビウス MEBIUS	1800	ZVW41N	2ZR-FXE(HYBRID)	13/4～		6.9	5.52	1.55	2.21	3.31	
					2.7	2.16	0.61	0.86	1.30	パワーコントロールユニット のクーラント	
ロッキー ROCKY	1000	A200S.A210S	1KR-VET	19/11～		4.7	3.76	1.06	1.50	2.26	
	1200	A201S	WA-FE	21/11～		4.2	3.36	0.95	1.34	2.02	
						4.1	3.28	0.92	1.31	1.97	
	1200	A202S	WA-FEX	21/11～		2.1	1.68	0.47	0.67	1.01	パワーコントロールユニット のクーラント